

2315 LED

LED weather-proof luminaire

- Multilumen and Multicolour
- Flexible mounting options
- Refurbishment solution

The 2315 G4 LED is the ideal weather-proof luminaire for car parks, storage areas, production areas and covered outdoor areas, for example. Multilumen, Multicolour and adjustable mounting clips make it the ideal 1:1 LED refurbishment solution. It can be surface-mounted to walls and ceilings as well as suspended, is very robust and easy and flexible to install. You'll master the job with it!



Why you'll get the job done with the 2315 G4 LED weather-proof luminaire

- Flexible adjustment of luminaire luminous flux and light colour thanks to Multilumen and Multicolour
- Easy and flexible installation thanks to quick connect system and adjustable mounting clips
- Variants with integrated through-wiring available.
- Suitable for wall, ceiling and suspended mounting.
- UV-stabilised polycarbonate – Robust and reliable.
- High efficiency (up to 117 lm/W).
- Reliable service life (50,000 h, L70).
- Removable driver and LED circuit board for optimised recycling of all components.

2315 LED at a glance

Dimensions	1.200: 1233 x 60,5 x 60 mm, 1270 x 60,5 x 60 mm (with through-wiring) 1.500: 1233 x 60.5 x 60 mm, 1570 x 60,5 x 60 mm (with through-wiring)
Luminaire luminous flux	1.200: 3.800 lm, 2.600 lm 1.500: 5.600 lm, 3.800 lm
Colour Temperature	Ra > 80 / 4.000 K, 6.500 K
Connected load	48 / 33 W, 32 / 22 W
Protection rating, Safety class	IP65 / IK08, SK I
Weight	1.200: 0,9 kg 1.500: 1,1 kg
Service life	50.000 h (L70)

All versions of 2315 G4 LED

product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions LxWxH [mm]	Replacement
Multilumen						
2315 G4 1200 38/26/ML-8MC ET PC	8427440	3.800 / 2.600	32 / 22	4.000	1.233 x 60,5 x 60	1 x 36 W 2 x 36 W
2315 G4 1500 55/38/ML-8MC ET PC	8427540	5.600 / 3.800	48 / 33	4.000 / 6.500	1.533 x 60,5 x 60	1 x 58 W 2 x 58 W
Multilumen with through-wiring						
2315 G4 1200 38/26/ML-8MC ET PC +LV	8427640	3.800 / 2.600	33 / 22	4.000 / 6.500	1.270 x 60,5 x 60	1 x 36 W 2 x 36 W
2315 G4 1500 55/38/ML-8MC ET PC +LV	8427740	5.600 / 3.800	48 / 33	4.000 / 6.500	1.570 x 60,5 x 60	1 x 58 W 2 x 58 W
CO₂ compensation / Multilumen with through-wiring						
2315 G4 S 1200 38/26/ML-840 ET PC +LV 	8428740	3.800 / 2.600	33 / 22	4.000	1.270 x 60,5 x 60	1 x 36 W 2 x 36 W
2315 G4 S 1500 55/38/ML-840 ET PC +LV 	8428840	5.600 / 3.800	48 / 33	4.000	1.570 x 60,5 x 60	1 x 58 W 2 x 58 W

All technical data as well as weight details and dimensions are carefully created. Errors are not excluded. Product pictures are an example and may differ from the original. We reserve the right to make changes that serve progress.