

2310 LED

LED Water-proof luminaire

- Wide distribution optic
- Refurbishment-friendly
- Adjustable luminaire luminous flux

The 2310 LED is the ideal weatherproof luminaire for e.g. multi-storey car parks, storage areas, production areas and canopied outdoor areas. The multi-lumen function, a variety of feed points and easy installation make it the ideal solution for one-to-one LED refurbishments. The possibility of replacing individual components at a later date provides it with a particularly long service life. This will get the job done!

Why you'll get the job done with the 2310 LED weatherproof luminaire

- Optimally suited for any lighting task due to wide distribution optic.
- Openability of the luminaire allows subsequent replacement of components and power supply via the rear of the luminaire.
- Can be flexibly positioned with up to 11 feed points and sliding mounting clips.
- Suitable for wall, ceiling and suspended mounting. Through-wiring as an accessory.
- Diffuser available in PC and PMMA materials.
- High efficiency (up to 122 lm/W).
- Reliable service life (50,000 h, L70).
- Flexible luminous flux setting thanks to multi-lumen function (6,000 lm and 4,000 lm)

2310 LED at a glance

Dimensions	1.200: 1257 x 102 x 91 mm 1.500: 1552 x 102 x 91 mm
Luminaire luminous flux	1.200: 4.000 lm 1.500: 6.000 lm, 4.000 lm (Multilumen)
Colour Temperature	Ra > 80 / 4.000 K
Connected load	33 W, 33/23 W
Protection rating, Safety class	IP66 / IK08, SK I
Weight	1.200: 2,3 kg 1.500: 2,6 kg
Lifetime	50.000 h (L70)

All versions of 2310 LED

product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions ØxH [mm]	Replacement
Switchable						
2310 12 B 40-840 ET PC	7922740	4000	35	4000	1257 x 102 x 91	1 x 36 W 2 x 36 W
2310 12 B 40-840 ET	7922840	4.000	35	4.000	1.257 x 102 x 91	1 x 36 W 2 x 36 W
Multilumen (adjustable luminaire luminous flux)						
2310 15 B 40/60/ML-840 ET PC	7922940	6.000 / 4.000	49 / 35	4.000	1.552 x 102 x 91	1 x 58 W 2 x 58 W
2310 15 B 40/60/ML-840 ET	7923040	6.000 / 4.000	49 / 35	4.000	1.552 x 102 x 91	1 x 58 W 2 x 58 W

Parts for 2310 LED

product reference	TOC	Description	Dimensions LxWxH [mm]	Weight
2310 ZLV/525/12	7923100	Through-wiring, 5-core 2.5 mm²	1257 x 102 x 91	0,2 kg
2310 ZLV/525/15	7923200	Through-wiring, 5-core 2.5 mm²	1552 x 102 x 91	0,2 kg

All technical data as well as weight details and dimensions are carefully created. Errors are not excluded. Product pictures are an example and may differ from the original. We reserve the right to make changes that serve progress.