

## 2325 LED

### Planar LED downlight

- Multilumen und Multicolour
- Sustainable luminaires: 2325 S
- Flexible mounting

The 2325 LED G3 downlight is the perfect option for lighting refurbishments due to its versatility and flexibility. Multilumen technology provides three luminaire luminous fluxes and Multicolour offers a choice of light colours in one luminaire. With refurbishment rings it is suitable for most ceiling openings. The 2325 LED is ideal for reception areas, hotels, restaurants, sales, exhibition, meeting and recreation rooms as well as corridors. Sustainable luminaires 2325 S with verified CO2 compensation. With this you master the job!



### Why you'll get the job done with the 2325 G3 LED downlight

- NEW: Multilumen and Multicolour: Adjustable luminous flux (2,000 lm, 1,400 lm, 800 lm) and light colors (3,000 K, 4,000 K)
- NEW: With refurbishment rings suitable for ceiling openings from 150 mm to 250 mm
- Toolless ceiling installation due to quick mounting springs
- Very low recess depth (43 mm incl. control gear unit)
- Pleasant light effect due to uniform illumination
- High efficiency (up to 105 lm/W).
- Reliable service life (50,000 h, L70)
- Sustainable luminaires 2325 S with higher efficiency and service life.

### 2325 LED at a glance

<b>Dimensions</b>	Ø 170 x 43 mm Ø 230 x 43 mm
<b>Luminaire luminous flux</b>	2.000 lm 1.400 lm 800 lm (Multilumen)
<b>Colour Temperature</b>	3.000 K 4.000 K
<b>Protection rating, Safety class</b>	IP20 IP44 (on room side) IK02
<b>Weight</b>	0,4 kg 0,5 kg
<b>Lifetime</b>	50.000 h (L70)

All versions of 2325 LED

product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions LxWxH [mm]	Replacement
CO2 compensation / Multilumen						
2325 G3 C05 S OA LED 20/14/08/ML-840 ET 	7790940	2000 / 1400 / 800		4000	Ø 170 x 43 mm	1 x 13 TC-TEL 1 x 18 TC-TEL   1 x 26 TC-TEL 1 x 32 TC-TEL   2 x 13 TC-TEL 2 x 18 TC-TEL
2325 G3 C07 S OA LED 20/14/08/ML-840 ET 	7791040	2000 / 1400 / 800		4000	Ø 230 x 43 mm	1 x 13 TC-TEL 1 x 18 TC-TEL   1 x 26 TC-TEL 1 x 32 TC-TEL   2 x 13 TC-TEL 2 x 18 TC-TEL

Multi-colour / multi-lumen (light colour and luminous flux adjustable)

2325 G3 C05 OA LED 20/14/08/ML-8MC ET	7791140	2000 / 1400 / 800	19 / 13 / 8	3000 / 4000	Ø 170 x 43 mm	1 x 13 TC-TEL 1 x 18 TC-TEL   1 x 26 TC-TEL 1 x 32 TC-TEL   2 x 13 TC-TEL 2 x 18 TC-TEL
2325 G3 C07 OA LED 20/14/08/ML-8MC ET	7791240	2000 / 1400 / 800	19 / 13 / 8	3000 / 4000	Ø 230 x 43 mm	1 x 13 TC-TEL 1 x 18 TC-TEL   1 x 26 TC-TEL 1 x 32 TC-TEL   2 x 13 TC-TEL 2 x 18 TC-TEL

Parts for 2325 LED

product reference	TOC	Description	Colour	Dimensions LxWxH [mm]	Weight
2325 G3 C05 SP 200	8120600	Mounting accessories / refurbishment ring for ceiling cutouts Ø 150 - 200 mm.	White	Ø 215 x 11	0,1 kg
2325 G3 C07 SP 250	8120500	Mounting accessories / refurbishment ring for ceiling cutouts Ø 200 - 250 mm	White	Ø 275 x 11	0,1 kg

All technical data as well as weight details and dimensions are carefully created. Errors are not excluded. Product pictures are an example and may differ from the original. We reserve the right to make changes that serve progress.