

2350 LED

LED surface-mounted luminaire

- Adjustable light colour and luminous intensity
- VDU workstation-compliant (UGR < 19)
- Wireless Connect types



The 2350 G4 is the tried-and-tested surface-mounted luminaire in the twenty3 portfolio. A square and two elongated designs make it the ideal lighting solution for offices, foyers and educational institutions, for example. Adjustable light colour and luminous intensity make them particularly flexible. Wireless Connect and DALI types enable use with lighting management systems. This way you will master the job!

Why you'll get the job done with the 2350 G4 LED surface-mounted luminaire

- Flexible setting of luminaire luminous flux due to multilumen
- Thanks to Multicolour, two light colours in one luminaire.
- 1:1 replacement of conventional luminaires during refurbishment.
- Optimised luminaire design for easy installation: separate frame and light unit.
- Pleasant light effect due to uniform illumination, suitable for VDU workstations (UGR < 19).
- High efficiency (up to 111 lm/W).
- Reliable service life (50,000 h, L70).

2350 LED at a glance

Dimensions

Square version (D): 602 x 602 x 50 mm
 Rectangular version (D2): 1202 x 302 x 50 mm
 Rectangular version (D3): 1502 x 302 x 50 mm

Luminaire luminous flux

Square version (D): 3600, 2900 lm
 Rectangular version (D2): 4000, 3000 lm
 Rectangular version (D3): 6000, 4000 lm

Colour Temperature

3.000 K, 4.000 K
 (Multicolour)

Protection rating, Safety class

Schutzart IP20/ IK02, Schutzklasse I

Weight

Square version (D): 2,8 kg
 Rectangular version (D2): 3,4 kg
 Rectangular version (D3): 4,2 kg

Lightmanagement

LiveLinkReady (ETDD)
 Wireless Connect (ETWD)

Lifetime

50.000 h (L70)

All variants of 2350 G4 LED

product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions LxWxH [mm]	Replacement
Switchable						
2350 G4 D PW19 36/29/ML-8MC ET	8537240	3.600 / 2.900	33 W / 25 W	4.000 / 3..000	602 x 602 x 50 mm	3 x 14 W / 4 x 14 W / 3 x 18 W / 4 x 18 W
2350 G4 D2 PW19 40/30/ML-8MC ET	8537340	4.000 / 3.000	36 W / 30 W	4.000 / 3.000	1.202 x 302 x 50 mm	2 x 28 W / 1 x 49 W / 1 x 58 W
2350 G4 D3 PW19 60/40/ML-8MC ET	8537540	6.000 / 4.000	54 W / 38 W	4.000 / 3.000	1.502 x 302 x 50 mm	2 x 28 W / 2 x 35 W / 2 x 58 W
DALI dimmable						
2350 G4 D2 PW19 4000-8MC ETDD	8537451	4.000	36 W	4.000 / 3.000	1.202 x 302 x 50 mm	2 x 28 W / 1 x 49 W / 1 x 58 W
2350 G4 D3 PW19 6000-8MC ETDD	8537651	6.000	54 W	4.000 / 3.000	1.502 x 302 x 50 mm	2 x 28 W / 2 x 35 W / 2 x 58 W
Wireless Connect						
2350 G4 D PW19 3600-8MC ETWD	8537965	3.600	33 W	4.000 / 3.000	602 x 602 x 50 mm	3 x 14 W / 4 x 14 W / 3 x 18 W / 4 x 18 W
2350 G4 D2 PW19 4000-8MC ETWD	8537765	4.000	36 W	4.000 / 3.000	1.202 x 302 x 50 mm	2 x 28 W / 1 x 49 W / 1 x 58 W
2350 G4 D3 PW19 4400-8MC ETWD	8537865	4.400	40 W	4.000 / 3.000	1.502 x 302 x 50 mm	2 x 28 W / 2 x 35 W / 2 x 58 W

All technical data as well as weight details and dimensions are carefully created. Errors are not excluded. Product pictures are an example and may differ from the original. We reserve the right to make changes that serve progress.