



2330 LED

LED recessed luminaire

- Light colour adjustable (multi-colour)
- Luminous flux adjustable (multi-lumen)
- VDU workstation-compliant

2330 LED is a recessed luminaire for system ceilings in 600 x 600 mm grid size. It scores points with pleasantly uniform light distribution and with UGR < 19 is suitable for VDU workstations. With adjustable light colour (multi-colour) and adjustable luminaire luminous flux (multi-lumen), the luminaire can be adapted to local conditions. Typical applications are offices, corridors, foyers, conference rooms, sales areas and waiting zones. This will get the job done!

Why you'll get the job done with the 2330 LED recessed luminaire

- Flexible use with multi-lumen and multi-colour: two luminous fluxes and light colours in one luminaire.
- Pleasant light effect due to uniform illumination, suitable for VDU workstations (UGR < 19).
- Separate control gear unit simplifies installation (and replacement).
- 1:1 replacement of conventional luminaires offering time and cost savings during refurbishment.
- Can be covered with insulation material
- High efficiency (up to 116 lm/W) and reliable service life (50,000 h, L65)
- Additional installation possibilities with suspension accessories (available separately)

2330 S - Sustainability at a glance

- Verified CO₂ compensation
- Higher energy efficiency: 120 lm/W
- Increased service life: 50,000 h, L70

2330 LED at a glance

Dimensions:	595 x 595 x 34 mm
Luminaire luminous flux:	3,600 lm, 2,900 lm (multi-lumen)
Colour Rendering Index:	Ra > 80
Colour Temperature:	3,000 K, 4,000 K (multi-colour), 6,500 K
Connected load:	31 W, 24 W
Protection rating, safety class:	IP20 / IK02 / I
Weight:	2.2 kg
Light management:	LiveLinkReady (ETDD) Wireless Connect (ETWD)

All versions of 2330 LED

Product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions L x W x H [mm]	Replacement
CO₂ kompensiert / Multilumen						
2330 G3 S M73 PW19 36/29/ML-840 ET	8332840	3600 / 2900	30	4000	595 x 595 x 34	3 x 14 / 4 x 14 / 3 x 18 / 4 x 18 W
Multi-colour / multi-lumen (light colour and luminous flux adjustable)						
2330 G3 M73 PW19 36/29/ML-830 ET	7632040	3400 / 2800	31 / 24	3000	595 x 595 x 34	3 x 14 / 4 x 14 / 3 x 18 / 4 x 18 W
2330 G3 M73 PW19 36/29/ML-840 ET	7631940	3600 / 2900	31 / 24	4000	595 x 595 x 34	3 x 14 / 4 x 14 / 3 x 18 / 4 x 18 W
2330 G3 M73 PW19 36/29/ML-865 ET	7767740	3600 / 2900	31 / 24	6500	595 x 595 x 34	3 x 14 / 4 x 14 / 3 x 18 / 4 x 18 W
2330 G3 M73 PW19 36/29/ML-8MC ET	7798540	3600 / 2900	31 / 24	3000 / 4000	595 x 595 x 34	3 x 14 / 4 x 14 / 3 x 18 / 4 x 18 W
DALI dimmable						
2330 G3 M73 PW19 3600-830 ETDD	7631851	3400	31	3000	595 x 595 x 34	3 x 14 / 4 x 14 / 3 x 18 / 4 x 18 W
2330 G3 M73 PW19 3600-840 ETDD	7631751	3600	31	4000	595 x 595 x 34	3 x 14 / 4 x 14 / 3 x 18 / 4 x 18 W
2330 G3 M73 PW19 3600-865 ETDD	7767651	3600	31	6500	595 x 595 x 34	3 x 14 / 4 x 14 / 3 x 18 / 4 x 18 W
Wireless Connect						
2330 G3 M73 PW19 3600-830 ETWD	7631865	3400	31	3000	595 x 595 x 34	3 x 14 / 4 x 14 / 3 x 18 / 4 x 18 W
2330 G3 M73 PW19 3600-840 ETWD	7631765	3600	31	4000	595 x 595 x 34	3 x 14 / 4 x 14 / 3 x 18 / 4 x 18 W

Parts for 2330 LED

Product reference	TOC	Description	Colour	Dimensions L x W x H [mm]	Weight
2330 G3 ZH/M73 M84	7716400	Suspension accessories	Zinc	100 x 80 x 15	0,2 kg