



2340 LED

LED wall luminaire and ceiling luminaire

- Multilumen and Multicolour
- Flexible to use with 2 sizes
- Optional sensors

The 2340 LED is super flexible in use. Whether as a wall or ceiling luminaire, it fulfils almost all lighting tasks thanks to multi-lumen technology in two stages per sizes. Applications consist of corridors, stairwells, entrance areas, relaxation rooms, hotels, restaurants, living areas, educational, health and care facilities. This will get the job done!

Why you'll get the job done with the 2340 LED wall and ceiling luminaire

- Flexible modification of luminaire luminous flux thanks to multi-lumen technology.
- Optionally with integrated HF motion sensor.
- Uniform front illumination with slight indirect ceiling or wall brightening.
- Replacement for conventional luminaires in refurbishment projects.
- Time savings due to quick and easy installation using functional bayonet catch and drilling template.
- High efficiency (up to 115 lm/W) and reliable service life (50,000 h, L65).

2340 LED at a glance

Dimensions:	WD 1: Ø 330 x 85 mm; WD 2: Ø 400 x 88 mm;
Luminaire luminous flux:	WD 1: 1.400, 800 lm (Multilumen) WD 2: 2.200, 1.600 lm (Multilumen)
Colour temperature:	3.000 K , 4.000 K (Multicolour)
Connected load:	WD 1: 12 W, 8 W WD 2: 19 W, 14 W
Protection rating, safety class:	IP20 / IK02/ I
Weight:	0,6 kg, 0,9 kg

All versions of 2340 LED

Product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions Ø [mm]	Replacement
Multi-colour / multi-lumen (light colour and luminous flux adjustable) with Sensor						
2340 G2 WD1 LED 14/08/ML-8MC ET+HFS	7790240	1400 / 800	12 W/ 8 W	4000 / 3000	Ø 330 x 85 mm	1 x 18 W / 1 x 26 W
2340 G2 WD2 LED 22/16/ML-8MC ET+HFS	7790440	2200 / 1600	19 W/ 14 W	4000 / 3000	Ø 400 x 88 mm	1 x 36 W TC-F
Multi-colour / multi-lumen (light colour and luminous flux adjustable)						
2340 G2 WD1 LED 14/08/ML-8MC ET	7790140	1400 / 800	12 W/ 8 W	4000 / 3000	Ø 330 x 85 mm	1 x 18 W / 1 x 26 W
2340 G2 WD2 LED 22/16/ML-8MC ET	7790340	2200 / 1600	19 W/ 14 W	4000 / 3000	Ø 400 x 88 mm	1 x 36 W TC-F