



2380 LED

LED highbay luminaires

- Sensor accessoires
- IP65
- Linsentechnik

The 2380 LED is a highbay luminaire for trade fair and exhibition halls, production facilities and warehouses. With IP65 it is also suitable for damp rooms and is available in three lumen packages. Single-point suspension means the luminaire is a simple 1:1 refurbishment solution. Optionally with sensor for particularly efficient lighting. This will get the job done!

Why you'll get the job done with the 2380 LED highbay luminaire

- Simple mounting thanks to single-point suspension small size and light aluminium housing
- Suspension kit available as an accessory
- 1:1 replacement of conventional luminaires offering time and cost savings during refurbishment
- HF motion sensor available as accessory, ZHAGA interface
- Efficient illumination of high halls thanks to lens optic with narrow-wide light distribution
- Service life 50,000 h (L65)

2380 LED at a glance

Dimensions:	Ø 268 x 145 mm Ø 310 x 145 mm
Luminaire luminous flux:	10.000 lm; 20.000 lm; 30.000 lm
Colour temperature:	4.000 K
Connected load:	77 W, 150 W, 200 W
Protection rating, Safety class:	IP65 / IK08 / I
Weight:	1,8 kg, 2,2 kg, 2,8 kg,

All versions of 2380 LED

Product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions LxWxH [mm]	Replacement
2380 G3 TB 10000-840 ET	7959440	10.000	77	4000	268 x 145	150 W HQI / HSE
2380 G3 TB 20000-840 ET	7959240	20.000	150	4000	310 x 145	250 W / 400 W HQL 250 W HQI / HSE
2380 G3 TB 30000-840 ET	7959340	30.000	200	4000	310 x 145	400 W HQI / HSE

Accessories for 2380 LED

Product reference	TOC	Description
2380 G3 HF SENSOR	7959500	Motion sensor
2380 G3 HF SENSOR RMC	7959600	Motion sensor / brightness sensor