



## 2390 LED

### LED floodlight

- Flexible to use with 2 sizes
- Universal mounting bracket
- Sensor accessories

The 2390 LED is a floodlight for illuminating outdoor areas such as construction sites, harbour and shipyard facilities, storage and container yards, as well as for accent lighting and spotlighting buildings. With two sizes and lumen packages, it offers ideal features for many applications. Universal mounting brackets for all mounting situations. This will get the job done!

#### Why you'll master the job with the 2390 LED floodlight

- Easy mounting due to the swivelling mounting bracket for hanging and standing installation
- Sensor available as accessory
- Time and cost saving 1:1 LED refurbishment solution
- 0.8 m connection cable
- Efficient illumination of large areas thanks to lens optics with medium-wide distribution characteristic
- Reliable service life (50,000 h, L65)

#### 2390 LED at a glance

<b>Dimensions (L x W x H):</b>	235 x 245 x 43 mm 320 x 345 x 50 mm
<b>Luminaire luminous flux:</b>	10.000 lm, 20.000 lm
<b>Colour temperature:</b>	3.000, 4.000 K
<b>Connected load:</b>	90 W, 180 W
<b>Protection rating, Safety class:</b>	IP65/IK08, I
<b>Weight:</b>	3,0 kg, 5,2 kg

#### All versions of 2390 LED

Product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions LxWxH [mm]	Replacement
2390 AM9R/10000-740 1G1W ET	7630940	10000	90	4000	235 x 245 x 43	HQI-TS 150W
2390 AM9R/10000-730 1G1W ET	7631040	10000	90	3000	235 x 245 x 43	HQI-TS 150W
2390 AM9R/20000-740 1G1W ET	7631140	20000	180	4000	320 x 345 x 50	HQI-TS 250W
2390 AM9R/20000-730 1G1W ET	7631240	20000	180	3000	320 x 345 x 50	HQI-TS 250W

#### Accessories 2390 LED

Product reference	TOC	Description	Dimensions LxWxH [mm]	Weight
2390 HF SENSOR	7641200	Motion sensor/Brightness sensor	70 x 35 x 100	0,1 kg